

**Code EA60SX – 60cm Stainless Steel Canopy**



**3 SPEED MOTOR**

This range hood provides the option of 3 different speed levels ensuring you have the option to use your range hood at a low, medium or high level of operation.

**HIGH EXTRACTION CAPACITY**

The extraction capacity of 700m<sup>3</sup>/hr provides strength and power to this stylish range hood.

**DISHWASHER SAFE CASSETTE FILTERS**

For easy cleaning, the cassette filters can be placed in a dishwasher and can easily be removed re-connected from the range hood.

**DECIBEL RATING**

54-60 dBa

**FEATURES**

- Stainless steel finish
- 3 speed motor
- 700m<sup>3</sup>/hr extraction capacity
- 2 x 20W halogen lights
- Separate light function
- Electronic button front controls
- Dishwasher safe cassette filters
- 150mm air flow outlet

**TIPS FOR BETTER USE**

- Leave your range hood on for 15 minutes after the cooking of the food to remove all odors, steam etc.
  - The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
  - It is recommended the range hood be installed between 650mm and 750mm above the cook top
  - It is also recommended that fumes from the range hood be ducted out into the atmosphere.
  - Turn off the range hood before attempting to clean
- Installation recommended by qualified installer**



Electronic button front control



20W halogen lights



Dishwasher safe cassette filter

**ELECTRICAL REQUIREMENT:**

Range hood is supplied with 10amp cord & plug.

**OPTIONAL ACCESSORIES**

**RECIRCULATING ACCESSORIES**

Carbon Filter Code: CF110 (requires x2)

**RANGEHOOD EXTENSIONS**

Flue Extension 1m Code: ERCEXT

**RANGEHOOD VENTILATION KITS**

RHKE65 – Wall – Eave vent kit

RHKMR65 – Universal metal roof kit, includes flashing

RHKTR65 – Universal tile roof kit, includes flashing

**FILTER CLEANING INFORMATION:**

Cassette mesh filter : requires cleaning monthly.

This will ensure no interruptions with airflow operation.

**PRODUCT DIMENSIONS**

