




# AUTOBOIL 25 LITRE WHITE

## Order Code 425052

Wall mounted instant boiling water appliance with integrates 0.2 micron MicroPurity™ filtration. The AutoBoil® employs twin chamber boiling water steam-heat-boost™ technology to recycle energy from steam to pre-heat the incoming cold water. The AutoBoil® has inbuilt self-calibration technology, utilises highly accurate electronic temperature control and incorporates a programmable digital display with 2 energy saving modes. The main boiling water tank is wrapped with high performance insulation to ensure the healthiest water and optimum efficiency. The AutoBoil® is equipped with an external two-way classic tap.



---

Manufacturing Code	425052
--------------------	--------

---

Capacity	25 L
----------	------

---

---

Water Pressure	Min 70kPa - Max 500kPa
----------------	------------------------

---

Water Connection	12.7mm BSP
------------------	------------

---

Power Rating	3.6kW 220-240 V 50Hz
--------------	----------------------

---

Dimensions	H786mm x W401mm x D301mm
------------	--------------------------

---

Product Approvals	WaterMark, CE
-------------------	---------------

---



Warranty	2 years
----------	---------

---

## Installation Requirements

1. Must be installed by a suitably qualified person in accordance with manufacturers instructions and with all relevant plumbing and electrical regulations. 2. In some hard water areas where mineral scale accumulation can become a problem, consideration should be given to the maintenance required, adding a high capacity filtration or water softening system should be considered.

## Installation Detail



Code (AU)	Code (NZ)	Description	W	D	H
415052	415652	15 Litre Autoboil	401	402	606
425052	425652	25 Litre Autoboil	401	402	786
440052	440652	40 Litre Autoboil	526	387	847

SCALE 1:6