



HYDROTAP G5 BCHA100 4-IN-1 CLASSIC TAP WITH CLASSIC MIXER CHROME



BOILING



CHILLED



HOT & AMBIENT

FILTERED

UNFILTERED

Order Code H51624Z00AU

Zip HydroTap Classic 4 in 1 Boiling, Chilled, Filtered water plus Hot and Cold washing up water from two separate taps. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration. Easy to install integrated ventilation tray included.



Manufacturing Code	H51624Z00AU
--------------------	-------------

Capacity	Commercial
----------	------------

Boiling Cups per hour	240
-----------------------	-----

Chilled Cups per hour	175
-----------------------	-----

Tap	Zip HydroTap CLASSIC Tap (Chrome)
-----	-----------------------------------

Water Pressure	Min 300kPa - Max 700kPa
----------------	-------------------------

Water Connection	1/2" BSP (G1/2)
------------------	-----------------

Water Supply Requirements	Cold
---------------------------	------

Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
--------------	--

Power Rating	2.1kW 220-240V 50Hz
--------------	---------------------

Booster Power Rating	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz
----------------------	---

Power Supply	2 x 10 Amp socket outlets
Dimensions	W395mm x D464mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Wels Rating	6 Star, 3.0 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com

Installation Detail

BK1.2 HydroTap G5 v1.01 03.21 BC40 BC60

Ventilation requirements

contact your local service provider if ventilation is not suitable

Clearance envelope
Position the Tap and the Command Centre as close together as possible.

Vent tray (kit no. 93540)

Detail A. Air inlet grille
Cut-out in cabinet floor

Detail B. Vent tray air outlet
Cut-out in cabinet floor

HydroTap Tap options

Classic Plus (116mm height, 216mm depth, 123mm width, 46mm hole)

Classic (116mm height, 208mm depth, 123mm width, 46mm hole)

Elite Plus (112mm height, 221mm depth, 134mm width, 46mm hole)

Touch-Free Wave (116mm height, 214mm depth, 123mm width, 46mm hole)

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap 35mm hole for Mixer Tap

Mixer Tap options

Arc Mixer Tap

Cube Mixer Tap

35mm hole on sink or benchtop

Classic Mixer Tap

Accessible Mixer Tap

35mm hole on sink or benchtop

Vented mixer tap installation

Only cold water supply required

35mm hole in sink/benchtop for mixer tap

RED marked braided hose to HydroTap Command Centre MIXER OUT

BLUE marked braided hose to HydroTap Command Centre MIXER IN

WHITE marked braided hose

Braided hose to HydroTap Command Centre MAINS inlet

Mains water isolation valve (not supplied)

Booster (BCS100 models)
Note: The 500mm braided hoses supplied cannot be lengthened

Clearance Envelope

IEC Flex & Plug 230-240V, 50Hz power outlet

Air inlet

Vent tray
Note: should not be impeded by pipework

Tee piece

Mains cold water isolation valve (not supplied)

4mm buffer pad air space

216mm

464mm

SCALE 1:5

ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

HydroTap G5

BC40 H, BC60 H, BC100 H

shown with "Classic Plus" Tap and Arc Mixer Tap (V)