

## Code EAF600SS – 60cm Fixed Rangehood Stainless Steel



### FEATURES

- Stainless steel with black front control panel
- 3 speed motor
- 200m<sup>3</sup> / hr extraction capacity
- 40W light
- Separate light function
- Recirculating option
- 120mm flue diameter

### EXTRACTION CAPACITY

The extraction capacity of 200m<sup>3</sup>/h

### QUIET NOISE LEVEL

A very quiet motor ensures the range hood has a very quiet noise level.

**Decibel Rating: 54 dBa**

### 3 SPEED MOTOR

This range hood provides the option of 3 different speed levels ensuring you have the option to use your range hood at a low, medium or high level of operation.

### RECIRCULATING OPTION

For installation where the unit can not be vented externally, this rangehood has the ability to recirculate the filtered air back in to the kitchen. A carbon filter can be installed as an optional extra. Carbon Filter Code: CFM60FVSS

### ELECTRICAL REQUIREMENT:

Range hood is supplied with 10amp cord & plug.

### RECIRCULATING ACCESSORIES:

Carbon Filter Code: CFM60FVSS (requires x1)

### RANGEHOOD VENTILATION KITS :

RHKE65 – Wall – Eave vent kit

RHKMR65 – Universal metal roof kit, includes flashing

RHKTR65 – Universal tile roof kit, includes flashing

### TIPS FOR BETTER USE

- After cooking leave your range hood on for a further 15 minutes to remove fumes
- The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- It is recommended the range hood be installed between 650mm and 750mm above the cook top
- It is also recommended that exhaust from the range hood be ducted out into the atmosphere
- Turn off the range hood before attempting to clean

**- Installation must be through qualified installer.**

### PRODUCT DIMENSIONS

