



HYDROTAP G5 B60 CLASSIC CHROME



BOILING

FILTERED

Order Code H51706Z00AU

Zip HydroTap Boiling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.



Manufacturing Code H51706Z00AU

Capacity Commercial

Boiling Cups per hour 160

Tap Zip HydroTap CLASSIC Tap (Chrome)

Water Pressure Min 170kPa - Max 700kPa

Water Connection 1/2" BSP (G1/2)

Water Supply Requirements Cold

Water Valves Integrated 500kPa Pressure limiting valve and Dual Check Valve

Power Rating 1.8kW 220-240V 50Hz

Power Supply 1 x 10 Amp socket outlet

Dimensions W280mm x D313mm x H333mm

Product Approvals WaterMark, RCM

Warranty 5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations. 2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product. 3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation. 4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service. 5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit. 6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

Installation Detail

BK1.2 HydroTap G5 v1.01.03.21 B, BA

Ventilation requirements <small>Contact your local service provider if ventilation is not suitable</small>		HydroTap Tap options	Font options
Clearance envelope Position the Tap and the Command Centre as close together as possible. 		Classic Plus Classic Elite Plus Touch-Free Wave 100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.	Raised Font with 135mm Extension part no. 95258 Font with 135mm Extension part no. 90915
	Tap Positioning Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory). 35mm hole for HydroTap Tap 	Cutting detail 	Cutting detail

HydroTap G5
B60, B100, BA60, BA100

shown with "Classic Plus" Tap

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.