

Caroma®

Uniset II Concorde Concealed


Plastic 6/3 litre Dual Flush
Connector Toilet Suite



Cl/SfB	(74.1)	g3
Date	November 2014	

Supersedes all previous issues

3.75.1





Uniset II Concorde Concealed



The **Uniset II Concorde Concealed** connector toilet suite with its mid sized cistern is designed for retrofit installations. This versatile 6/3 litre dual flush suite is suitable for multi purpose applications and can be used where authorised for septic installations.

- Pans:** **Concorde Concealed** 6 litre full flush washdown pan
- Traps:** S-trap and P-trap.
- Inlet:** 50mm back inlet 40mm key seal is available if required.
- Cistern:** **Uniset II** cistern – is a one piece injection moulded tank with a well fitting removable lid housing and centrally positioned push buttons and incorporates a quiet inlet valve to reduce noise during the filling cycle.
- Inlet Valve** **Standard Bottom Inlet Cistern** – available as right hand inlet which is interchangeable and incorporates the Apollo inlet valve. Overflow is internal as standard, external overflow kit available. **Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant.**
- Overflow:**
- Seat and Connector Plate:** The **Tasman** standard seat or the **Caravelle** soft close seat and connector plate is supplied as standard with this suite. See chapter 5.01 SEATS of the Caroma Technical Manual for further details.
- Colours:** White (W) and Ivory (I)
- Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.
- Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

