

SN 10 SLi

SMALL WATER HEATERS 5 TO 15 L

PRODUCT-NO.: 222193

The SN small water heater is designed to supply one draw-off point and is mounted over the sink. The appliances can be adjusted to anywhere between 35 °C and 85 °C, making water with a consistent temperature available at all times. The high limit safety cut-out provides a constant and safe maximum water temperature. As an option, this can be set to 38 °C, 45 °C, 55 °C or 65 °C. The highly effective thermal insulation used in the small water heaters minimises energy losses.



The main features

Small water heater, 10 litre capacity

For a single draw-off point

Low standby loss power consumption

Splashproof to IP 24

Economy setting 60 °C

Plug-in unit for electrical connection to any standard socket



Type	SN 5 SLi	SN 10 SLi
Part no.	221127	222193
Connected load	2 kW	2 kW
Width	263 mm	295 mm
Depth	230 mm	275 mm
Height	421 mm	503 mm

Technical data

Rated voltage 1	220 V	220 V
Rated output 1	1,8 kW	1,8 kW
Rated current 1	8,3 A	8,3 A
Fuse 1	10 A	10 A
Rated voltage 2	230 V	230 V
Rated output 2	2,0 kW	2,0 kW
Rated current 2	8,7 A	8,7 A
Fuse 2	10 A	10 A
Rated voltage 3	240 V	240 V
Rated output 3	2,2 kW	2,2 kW
Rated current 3	9,1 A	9,1 A
Fuse 3	10 A	10 A
Frequency	50/60 Hz	50/60 Hz
Phases	1/N/PE	1/N/PE
Rated capacity	5 l	10 l
Power supply	1/N/PE	1/N/PE
Standby energy consumption/24 h at 65 °C	0,2 kWh	0,3 kWh
Colour	white	white

IP-Rating	IP24 D	IP24 D
Energy efficiency class	A	A
Weight	3,2 kg	4,6 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.