

Sanicom®2

Sanicom® 2 is a commercial grey water lifting station featuring two powerful motors, ensuring continuity of service for your business.

WHY CHOOSE THIS PRODUCT?

Ideal for heavy commercial applications

Safe, reliable twin motor pump for continuity of service

Unit operates automatically

1/65 mm rear and two 80 mm side entries and air vent connection for external venting

Working temperature of 35°C

Will handle up to 90°C for short periods (5 minutes)

External hard-wired alarm


Alternates duty cycle

2 x pre mounted non return valves (supplied)

2 m pre wired cable

VERTICAL/HORIZONTAL PERFORMANCE


Increase size of horizontal run by one pipe size after 5m. All horizontal pipework requires a minimum of 1:100 fall.



20 30 40 50 60 70 80 90 100 110 metres


TECHNICAL CHARACTERISTICS

Discharge Pipework	40/50 mm
Motor Power	1500 Watts x 2
Voltages	220-240 V/50 Hz
Tank Volume	34.5 L
Working Waste Water Temp	35°C/Max 90°C (intermittent)
Product Weight	26 kg
Overall Measurements	582 x 486 x 529 mm
Inlet Pipework	50/65/80 mm
IP Rating	IP44



FLOW RATE PERFORMANCE CHART

Discharge height (m)



P1 - Output flow rate with one motor engaged OUTPUT P1 + P2 - Output flow rate with two motors engaged (litres/min)

APPLICATIONS











SHOWER WASHING MACHINE





DISH WASHER

KITCHEN




PRODUCT REFERENCE: SA108



Wired alarm panel



External mounted control box





Shaking up water

Made in France to the highest standards, needs to be installed by a licensed plumber